

## ZEPHIRO FOG 900

900 Watt Fog Machine with wired and wireless control

It is well known how the world of show business and entertainment is based on the fusion of music, images, lights and environmental effects. The sensory involvement of those who enjoy the entertainment event is increasingly present nowadays. Centolight knows very well this need and thanks to the Zephiro line it offers a wide range of machines for smoke, fog, bubbles, snow and more.

Zephiro Fog 900 is a powerful and compact fog machine; designed for professional small to medium on-stage applications and equipped with wired and wireless control. It can generate a persistent and homogeneous fog that greatly enhances visual effects and light beams of any type of fixtures in settings such as theaters, photo and TV studios, film sets, discos, live events, etc.

It has a power output of 900W and is designed for indoor applications with an output of  $140 \, \text{m}^3$ /minute. Consumption is about 1L/hour of continuous emission (depending on liquid density). The internal tank is 1 liter.







## PRODUCT DETAILS

## Key features

140m³/Minute smoke output fills up a small/medium sized room quickly

Continuous smoke output after about 3 minutes warm-up time

1L Tank capacity for about 2-hour continuous use without refilling

Wired and wireless controllers

## Specifications

| Heating Element            | 900 Watt                                 |
|----------------------------|--|
| Output distance            | 2-3 meters                               |
| Warm-up time               | Approximately 3 Minutes                  |
| Tank capacity              | 1 Liter                                  |
| Fog output                 | 140m³/Min                                |
| Ready-indicator            | Led indicator on rear panel              |
| Wireless remote controller | 433,92 MHz (Max 10 Meters)               |
| Wired remote controller    | Start/Stop switch                        |
| Mounting bracket           | Included                                 |
| Power requirements         | 220V AC, 50Hz                            |
| Internal fuse              | 10A 250V fast blow 20mm glass            |
| Dimensions                 | 345 x 205 x 185 mm (13.6 x 8.1 x 7.3 in) |
| Weight                     | 3,4 Kg - 7.5 lbs.                        |
| Packing Size               | 410 x 250 x 230 mm (16.1 x 9.8 x 9 in)   |
| Packing Weight             | 4,4 kg - 9.7 lbs.                        |