

## THESIS-1940Z-SET

Set of 2 19x40w wash moving heads with flight case

The **Thesis 1940z** is a next-generation moving head wash, powerful and incredibly versatile, designed to enhance the quality of stage effects in any type of event, be it live shows, concerts, theaters, or television studios. Thanks to its **19 RGBW LEDs of 40W** and **76 RGB SMD LEDs**, it offers an exceptionally uniform and precise color mixing, allowing lighting designers to create unique and captivating visual atmospheres. The **integrated pixel ring** adds further dynamism, amplifying the scenic impact through sophisticated light effects that grab the audience's attention. One of the key features of the Thesis 1940z is its **motorized zoom**, which ranges widely from **6° to 60°**, allowing smooth transitions from concentrated and penetrating beams to broader and more diffused wash effects. This flexibility makes it adaptable to any stage setup and scene requirements, making it particularly suitable for high-quality productions where visual versatility is crucial.

A distinctive aspect of the **Thesis 1940z** is its advanced **pixel control**, which allows each individual LED to be programmed and controlled independently, enabling the creation of an infinite range of **customized effects** and **dynamic light shows**. This feature allows lighting designers to craft complex and engaging patterns, such as undulating pixel movements, cascading effects, or synchronized flashes, further enhancing the visual impact of the performance. With this technology, constantly evolving visual effects can be achieved, keeping the audience's attention and adapting to every phase of the show. The **standard DMX control** and optional **Art-Net** ensure practical and flexible device management, simplifying programming operations and effect synchronization. This makes it perfect not only for large live events but also for permanent installations or television productions where precision and speed are essential.

Furthermore, the Thesis 1940z is designed to ensure **silent operation** and **precise movements**, thanks to the adoption of **3-phase motors**, which enable smooth and flawless transitions without disturbing the surrounding environment—a particularly important factor in quiet settings such as TV studios or theaters.

Ideal for those seeking a reliable and technologically advanced solution, the Thesis 1940z represents excellence in the field of professional lighting, delivering high-level performance and maximum versatility for any type of production.





## PRODUCT DETAILS

### Key features

Powerful lighting with 19 RGBW LEDs of 40W with intense and uniform color output.

---

Advanced pixel mapping to create unique and customised effects.

---

Advanced scenic effects with The pixel ring allows for spectacular dynamic light shows.

---

Versatile zoom with wide range from 6° to 60°, perfect for both beam and wash effects.

---

Silent movements with 540° PAN and 250° TILT with 3-phase motors, ideal for environments requiring precision.

---

Efficient cooling for prolonged and silent operation.

---

Ease of use with clear and intuitive LCD display for quick parameter navigation.

---

Robust design with compact and durable structure, suitable for intensive use.

---

Integrated presets with predefined effects and programs for quick setup.

---

## Specifications

<b>Light source</b>	19 x 40W 4-in-1 RGBW LEDs + 76 x 0.2W SMD RGB LEDs.
<b>Life Span</b>	50000H
<b>lens</b>	high efficiency acrylic 19 PCS
<b>Zoom</b>	linear motorised 6°-60°, smooth and silent.
<b>PAN</b>	540° movement (8/16 bit)
<b>TILT</b>	250° movement (8/16 bit)
<b>Colours</b>	Sophisticated mixing managed by RGBW software
<b>CTO</b>	Linear colour temperature adjustment
<b>Macro</b>	preset colours
<b>Pixel selections</b>	Various static and dynamic shape selections with variable speed
<b>Background effects</b>	Options of background colours with dimmers from 0 to 100 per cent.
<b>Pixel strip</b>	ring-shaped LEDs for adjustable visual effects.
<b>Strobe</b>	1-25T/sec high-speed shutter/strobe with variable speed
<b>Dimmer</b>	0-100% homogeneous LED linear
<b>DMX channels</b>	25/39/82/115
<b>Power supply</b>	electronic AC90-240V 50/60Hz
<b>Power consumption</b>	760W
<b>Ambient temperature</b>	-25 to 45
<b>Degree of protection</b>	IP20
<b>Net weight</b>	15.2 kg
<b>Gross weight</b>	18.7 kg
<b>Product dimensions</b>	231(W)*405(D)*440(H)mm
<b>Packaging dimensions</b>	390(D)*620(W)*510(H)mm