

PORTRAIT-412 SET

Set of 8 LED PAR 4x12W RGBW 4in1 with lithium battery and flight case with charging function

PORTRAIT-412 is a battery-powered (or mains-powered) PAR, specifically designed for rental applications. You can easily control it by choosing among IR remote control, wired DMX-512 connection, Wireless DMX (by using the SOUNDSTATION AIRCOM-126, 2.4GHz Wireless DMX Transceiver - check www.soundsationmusic.com for further details), and Wi-Fi Control by using LED LAMP free APP for iOS® and Android® devices. This fixture is part of a set composed by 8pcs PARs housed in a flight case with charging function. You can easily recharge by placing them in the flight case, connecting to power with the eight IEC connectors, and finally connecting the flight case external power connector to a mains outlet. The lighting emitting system consists of 4pcs 12W RGBW 4in1 high-brightness LEDs with a life-span of approximately 50,000 hours. Each LED features a high-quality lens with 15° beam angle and 29° field angle, making this PAR ideal for all applications ranging from wash to beam use. The PORTRAIT-412 has a highly compact housing, and can be fit inside 300x300mm truss to create wonderful wash effect inside the truss structure. The fixture can sit on even and solid floor and work as an up-light. It also has a built-in adjustable tilt support. By pushing the tilt support, the fixture tile can move up to 25° to wash walls or facades. The high-efficiency lithium battery guarantees a complete charge from zero within about 5 hours, and a working duration ranging from 5 hours (full color mode) to 12 hours (single color mode). The infrared remote control allows remote control of the main functions without the use of DMX.

WIRELESS TRANSMITTER ON REQUEST

Please refer to code PRT0889



PRODUCT DETAILS

Key features

4x 12W RGBW 4in1 high-efficiency and long-life LEDs

15° Beam angle; 29° Field angle

Wireless 2.4GHz DMX-512 control

DMX-512 wired control

Wi-Fi Control Mode

IR remote control

0°-25° adjustable tilt support

Foldable handle for easy transport

OLED Color Display with intuitive interface

Rechargeable Lithium-Ion Battery for up to 12-hour operation

8-Units Flight Case with Charging Function

FOR WIRELESS TRASMITTER Please refere to code PRT0889

Specifications

Light sources	4x12W RGBW 4-in-1 LEDs
Beam angle	15°
Field angle	29°
Led average life span	50,000 hours
Control mode	DMX512, Master/Slave, Stand Alone, Wireless DMX, IR Remote Control, Wi-Fi control
DMX channel	4/8 channel selectable
Control panel	LCD display
Power input	100-240VAC 50/60Hz
Power consumption	Max. 45W
Fuse	F5A-250V
Connettore di ingresso / uscita alimentazione	IEC Ingresso / Uscita
Battery type	Rechargeable lithium-ion Battery Pack 14.8V - 5.2Ah LG18650-4S2P
Battery Pack Size	65 x 75 x 35 mm
Charge time	About 5.0 hours
Battery life	5 hours at full color from one full charge; 8 hours at running preset programs; 12 hours at running single color
IP rating	IP20
Cooling	Natural cooling, silent operation
Housing Material	Rigid metal
Housing color	Black
Fixture Size	138 x 144 x 205mm
Net weight	3.6 kg
WIRELESS TRANSMITTER	Please refer to code PRT0889